

Bearing Unit No.	Shat DiaMM (mm)	Dimensions (mm)										Bolt Used		Weight (kg)	Dyn. C,KN	Stat. C,KN
		h	a	e	b	S2	S1	g	w	Bi	n	(in)	(mm)			
UCP305	25	45	175	132	45	20	17	15	85	38	1/2	15	M14	0,90	17,2	11,5
UCP306	30	50	180	140	50	20	17	18	95	43	1/2	17	M14	1,10	20,8	15,2
UCP307	35	56	210	160	56	25	17	20	106	48	1/2	19	M14	1,95	25,8	19,2
UCP308	40	60	220	170	60	27	17	22	116	52	1/2	19	M14	2,20	31,2	24
UCP309	45	67	245	190	67	30	20	24	129	57	5/8	22	M16	3,30	40,8	31,8
UCP310	50	75	275	212	75	35	20	27	143	61	5/8	22	M16	4,80	47,5	37,8
UCP311	55	80	310	236	80	38	20	30	154	66	5/8	25	M16	5,30	55	44,8
UCP312	60	85	330	250	85	38	25	32	165	71	3/4	26	M20	6,30	62,8	51,8
UCP313	65	90	340	260	90	38	25	33	176	75	3/4	30	M20	8,00	72,2	60,5
UCP314	70	95	360	280	90	40	27	35	187	78	7/8	33	M22	8,30	80,2	68
UCP315	75	100	380	290	100	40	27	35	198	82	7/8	32	M22	9,50	87,2	76,8
UCP316	80	106	400	300	110	40	27	40	210	86	7/8	34	M22	12,50	8,65	94,5
UCP317	85	112	420	320	110	45	33	40	220	96	1	40	M27	14,50	102	96,5
UCP318	90	118	430	330	110	45	33	45	235	96	1	40	M27	20,40	110	108
UCP319	95	125	470	360	120	50	36	45	250	103	1-1/8	41	M30	22,30	120	122
UCP320	100	140	490	380	120	50	36	50	275	108	1-1/8	42	M30	25,00	132	140
UCP321	105	140	490	380	120	50	36	50	280	112	1-1/8	44	M30	24,00	142	152
UCP322	110	150	520	400	140	55	40	55	300	117	-	46	M33	27,50	158	178
UCP324	120	160	570	450	140	55	40	65	320	126	-	51	M33	32,30	175	208
UCP326	130	180	600	480	140	55	40	75	355	135	-	54	M33	41,00	195	242
UCP328	140	200	620	500	140	55	40	75	390	145	-	59	M33	50,00	212	272