

ISO	Shaft Dia MM	o	g	p	q	s	b	k	e	a	w	j	l	h	t	z	Bi	n	Bolt size	Dyn. Cr N	Stat. Co N
UCT 201	12	16	10	51	32	19	51	12	76	89	94	32	21	61	2	51	31,0	12,7	31,0	7,35	4,78
UCT 202	15	16	10	51	32	19	51	12	76	89	94	32	21	61	2	51	31,0	12,7	31,0	7,35	4,78
UCT 203	17	16	10	51	32	19	51	12	76	89	94	32	21	61	2	51	31,0	12,7	31,0	7,35	4,78
UCT 204	20	16	10	51	32	19	51	12	76	89	94	32	21	61	2	51	31,0	12,7	31,0	9,88	6,65
UCT 205	25	16	10	51	32	19	51	12	76	89	97	32	24	62	2	57	34,1	14,3	34,1	10,8	7,88
UCT 206	30	16	10	56	37	22	57	12	89	102	113	37	28	70	2	62	38,1	15,9	38,1	15	11,2
UCT 207	35	16	13	64	37	22	64	12	89	120	129	37	30	78	3	72	42,9	17,5	42,9	19,8	15,2
UCT 208	40	19	16	83	49	29	83	16	102	114	144	49	33	88	3	82	49,2	19,0	49,2	22,8	18,2
UCT 209	45	19	16	83	49	29	83	16	102	117	144	49	35	87	3	82	49,2	19,0	49,2	24,5	20,8
UCT 210	50	19	16	83	49	29	86	16	102	117	149	49	37	90	3	87	51,6	19,0	51,6	27	23,2
UCT 211	55	25	19	102	64	35	95	22	130	146	171	64	38	106	4	92	55,6	22,2	55,6	33,5	29,2
UCT 212	60	32	19	102	64	35	102	22	130	146	194	64	42	119	4	102	65,1	25,4	65,1	36,8	32,8
UCT 213	65	32	21	111	70	41	121	26	151	167	224	70	44	137	4	107	65,1	25,4	65,1	44	40
UCT 214	70	32	21	111	70	41	121	26	151	167	224	70	46	137	-	-	74,6	30,2	74,6	46,8	45

UCT 215	75	32	21	111	70	41	121	26	151	167	232	70	48	140	-	-	77,8	33,3	77,8	50,8	49,5
UCT 216	80	32	21	111	70	,41	121	26	165	184	235	70	51	140	-	-	82,6	33,3	82,6	55	54,2
UCT 217	85	38	29	124	73	48	157	30	173	198	260	73	54	162	-	-	85,7	34,1	85,7	64	63,8
UCT 218	90	40	30	130	80	48	140	30	190	215	275	80	55	170	-	-	96,0	39,7	96,0	73,8	71,5